



## Product Specifications of Nippi Collagen Casings

### Nippi Collagen Casing R-Type (11/12/15 meters strand)

Size code	Diameter (mm)	Strands per caddy	Meters per caddy	Meters per carton/case	Flat width of unshirred casing (mm)
130	Approx. 13.0 mm	15m x 112 strands	1,680m	15,120m	19.0-20.0mm
140	14.0	15 x 104	1,560	14,040	20.0-21.0
150	15.0	15 x 84	1,260	11,340	21.0-22.0
160	16.0	15 x 84	1,260	11,340	22.0-23.0
170	17.0	15 x 77	1,155	10,395	23.0-24.0
180	18.0	15 x 77	1,155	10,395	24.0-25.0
190	19.0	15 x 66	990	8,910	25.0-26.0
200	20.0	15 x 60	900	8,100	26.0-27.5
210	21.0	15 x 54	810	7,290	27.5-29.0
220	22.0	15 x 54	810	7,290	29.0-30.5
230	23.0	15 x 45	675	6,075	30.5-32.0
240	24.0	15 x 40	600	5,400	31.5-33.0
250	25.0	15 x 40	600	5,400	33.0-34.5
260	26.0	15 x 35	525	4,725	34.5-36.0
270	27.0	15 x 35	525	4,725	36.0-37.5
280	28.0	15 x 28	420	3,780	37.5-39.0
290	29.0	15 x 28	420	3,780	39.0-40.5
300	30.0	15 x 28	420	3,780	40.5-42.0
310	31.0	15 x 24	360	3,240	42.0-44.0
320	32.0	15 x 24	360	3,240	44.0-46.0
330	33.0	12 x 24	288	2,592	46.0-48.0
340	34.0	12 x 21	252	2,592	48.0-50.0
350	35.0	11 x 21	231	2,079	50.0-52.0
360	36.0	11 x 21	231	2,079	52.0-54.0
370	37.0	11 x 20	220	1,980	54.0-56.0
380	38.0	11 x 18	198	1,782	56.0-58.0

### Nippi Collagen Casing R-Type (18 meters strand)

Size code	Diameter (mm)	Strands per caddy	Meters per caddy	Meters per carton/case	Flat width of unshirred casing (mm)
170	Approx. 17.0mm	18m x 77 strands	1,386m	12,474m	23.0-24.0mm
180	18.0	18 x 77	1,386	12,474	24.0-25.0
190	19.0	18 x 66	1,188	10,692	25.0-26.0
200	20.0	18 x 60	1,080	9,720	26.0-27.5
210	21.0	18 x 54	972	8,748	27.5-29.0
220	22.0	18 x 54	972	8,748	29.0-30.5
230	23.0	18 x 45	810	7,290	30.5-32.0

Other casing types and sizes are available- please contact your local Nippi specialist for details.

Specifications may be changed without prior notice.

Average flat width throughout one strand of casing must fall within our specifications.

Diameter indicates maximum millimeters in case of straight stuffing using brake ring.



# Nippi. Incorporated

## Collagen Division

HEAD OFFICE  
1-1-1 Senjumidori-cho Adachi-ku  
Tokyo 120-8601 Japan  
TEL +81-3-3888-5112

FUJINOMIYA PLANT  
1 Yumizawa-cho, Fujinomiya  
Shizuoka 418-0073 Japan  
TEL +81-544-23-7111

SHIBAKAWA PLANT  
395-1 Kamiyuno Fujinomiya  
Shizuoka 419-0301 Japan  
TEL +81-544-29-3000

### Nippi Collagen Casing F-Type (15 meters strand)

Size code	Diameter (mm)	Strands per caddy	Meters per caddy	Meters per carton/case	Flat width of unshirred casing (mm)
180	Approx. 18.0mm	15m x 77 strands	1155m	10,395m	24.0-25.0mm
190	19.0	15 x 66	990	8,910	25.0-26.0
200	20.0	15 x 60	900	8,100	26.0-27.5
210	21.0	15 x 54	810	7,290	27.5-29.0
220	22.0	15 x 54	810	7,290	29.0-30.5
230	23.0	15 x 45	675	6,075	30.5-32.0
240	24.0	15 x 40	600	5,400	31.5-33.0
250	25.0	15 x 40	600	5,400	33.0-34.5
260	26.0	15 x 35	525	4,725	34.5-36.0
270	27.0	15 x 35	525	4,725	36.0-37.5
280	28.0	15 x 28	420	3,780	37.5-39.0
290	29.0	15 x 28	420	3,780	39.0-40.5
300	30.0	15 x 28	420	3,780	40.5-42.0
310	31.0	15 x 24	360	3,240	42.0-44.0
320	32.0	15 x 24	360	3,240	44.0-46.0

### Nippi Collagen Casing F-Type (18 meters strand)

Size code	Diameter (mm)	Strands per caddy	Meters per caddy	Meters per carton/case	Flat width of unshirred casing (mm)
200	Approx.20.0 mm	18m x 60 strands	1,080m	9,720m	26.0-27.5
210	21.0	18 x 54	972	8,748	27.5-29.0
220	22.0	18 x 54	972	8,748	29.0-30.5
230	23.0	18 x 45	810	7,290	30.5-32.0

### Nippi Collagen Casing F-Type (30 meters strand)

Size code	Diameter (mm)	Strands per caddy	Meters per caddy	Meters per carton/case	Flat width of unshirred casing (mm)
210	Approx. 21mm	30m x 35 strands	1,050 m	9,450m	27.5-29.0mm
220	22	30 x 35	1,050	9,450	29.0-30.5
230	23	30 x 28	840	7,560	30.5-32.0
280	28	30 x 18	540	4,860	37.5-39.0

Other casing types and sizes are available- please contact your local Nippi specialist for details.

Specifications may be changed without prior notice.

Average flat width throughout one strand of casing must fall within our specifications.

Diameter indicates maximum millimeters in case of straight stuffing using brake ring.